ICY BOX®

www.icybox.de

IB-CAM2002

IP Bullet Camera, Outdoor IP66, Sensor: 1.3MP 1/2.7" CMOS, IR LEDs

KEY FEATURES

- Supports H.264, MPEG-4 and MJPEG – triple codec compression with multiple streams
- 1/2.7" progressive scan CMOS sensor
- 1.3 Megapixel resolution up to 1280x1024 pixel
- Up to 30fps @ HD720
- Bundled with CS mount: 6mm/F1.8 megapixel fixed lens with IR correction
- Built-in IR illuminators, IR working distance up to 15M
- Day & night function with mechanical IR cut filter
- Digital input for external sensor
- Built-in 802.3af compliant PoE
- Weather-proof IP66 rated (aluminum) housing
- Supports ONVIF standard to ensure interoperabilit

Versatile Security, Reliably Manageable

The ICY BOX IB-CAM2001 is a weather-proof surveillance camera for exteriors with excellent optical features. More than that, it has features, which make possible the safeguarding of valuable assets in a broad range of environments.

The combination of a huge sensor chip, 2.7" (CMOS), 1.3 megapixels and a lens with the great aperture of 1/1.8 allows for a wide area of use with high clarity and solution.

The comprehensive event management allows for an active surveillance of movements. When needed, the 24 IR LEDs will be switched on (camera has IR cut filter), external floodlights or sirens can be activated. Messaging is possible via email or FTP. The software manages up to 16 cameras, provides live video, stores the recordings and makes them available when needed.

RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany
Telefon: +49-(0)4102 – 468 900 (Vertrieb) • Fax: +49-(0)4102 – 468 901 • www.raidsonic.de
Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.

ICY BOX®

www.icybox.de

TECHNICAL DATA

Model	**IB-CAM2002**
Article No.	80423
EAN code	4250078185338
Brand	ICY BOX
Category	IP Camera
Article text	IP Bullet Camera, Outdoor IP66, Sensor: 1.3MP 1/2.7" CMOS, IR LEDs
Colour	White
Material	Metal
Lens	• CS mount • Fixed iris • Focal length 6.0mm • Aperture F1.8
Shutter Time	• Up to 1/960 sec.
Image Sensor	• 1.3 Megapixel Progressive Scan 1/2.7" CMOS
Minimum Illumination	• 0.5 Lux / F1.8 • 0 Lux / IR-LEDs
IR Illuminators	• 24x IR LED, 15m
Video Compression	• H.264 • MPEG-4 • MJPEG • 30fps 1280 x 1024 up to 30fps at HD720
Image Settings	• ICR (Removable IR-cut filter) for day & night vision • AEC • AWB • WDR • Brightness • Contrast • Saturation • Sharpness • Mirror • Flip • OSD: Timestamp, Text caption overlay and privacy mask

Audio		• Ext. Mic In • Audio Out
Networking		• 10/100 Mbps Ethernet, RJ-45 • Protocols: IPv4, TCP/IP, HTTP, HTTPs, UPnP, RTSP/RTP/RTCP, IGMP, FTP, DHCP, DNS, DDNS, PPPoE, NTP, SMTP • ONVIF compatible
Alarm and Event Management	**Alarm**	• Motion detection • Digital input • Manual alarm
	Event	• Digital output • Notification via email or FTP with attached video file or screenshot
On-board Storage		No
Security		• Multi-level user access with password protection • IP address filtering • HTTPS encrypted data transmission
Users		• 10 for webinterface • 16 for software
LED Indicator		• System activity and network link indicator
Power connector		• DC 12 V/2 A AC 24 V • PoE IEEE 802.3af compatible
Interfaces/Buttons		• 1 x RJ45 ethernet LAN connector • 2 x Headphone jacks (Ext. Mic. x 1, Audio out x 1) • 1 x 12 V DC Jack • 10-pin terminal block for RS-485 / Digital input / Digital output / GND / Reset

PACKING CONTENT	IB-CAM2002, Software CD, Power supply, Manual, Mounting bracket

LOGISTICAL DATA

Packing unit	x pcs./carton
Total weight	x kg/carton
Gross weight (incl. packing)	x kg
Net weight	0.906 kg

Dimension/carton	x mm
Dimension of packing box	x mm
Dimension of article	85x85x180 mm
Country of origin	Taiwan
Import tax	8525801990

RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany
Telefon: +49-(0)4102 – 468 900 (Vertrieb) • Fax: +49-(0)4102 – 468 901 • www.raidsonic.de
Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.